

40161 Highway 59 Yuma, CO 80759 www.irf-info.com



IRRIGATED CORN VARIETY TRIALS

FARMREIGN PRECISION PLANTER PLANTING DATE: 5/9/2018

HARVEST DATE: 10/28/2018 B SE 1/4 FIELD:

POPULATION: 34K LG 5548 STX RIB VARIETY:

APPLICATION DATE PREVIOUS CROP: Corn

(Analysis) 4 - 8 - 1 - 4.6s DMI STRIP-TILL:

applied at 10 gal./A @ 4" and 13 gal./A @ 10" 3/29/2018

(Analysis) 16 - 9 - 3 - 2.6s - .1zn 18 gal./A 5/9/2018 2X2 STARTER FERTILIZER:

28 - 0 - 0 - 5 @ 5 gal./A 5/27/2018 THROUGH REINKE SPRINKLER: 6/13/2018 28 - 0 - 0 - 5 @ 10 gal./A

7/2/2018 28 - 0 - 0 - 5 @ 5 gal./A

28 - 0 - 0 - 5 @ 7.5 gal./A 7/6/2018 28 - 0 - 0 - 5 @ 2.5 gal./A 7/9/2018

28 - 0 - 0 - 5 @ 6 gal./A 7/17/2018

28 - 0 - 0 - 5 @ 6 gal./A 7/20/2018 28 - 0 + 0 - 5 @ 6 gal./A 7/24/2018

RAINFALL: APPLIED WATER: **13.50** inches **12.32** inches

May - 2.33", June - 5.91", July - .63", August - 1.89", September - .47", October - 1.4" **RAINFALL by MONTH:**

GROUND SPRAY APPLICATIONS: ACURON @ 1.5 qt./A + ROUNDUP POWERMAX @ 32 oz./A +

5/16/2018 AMS @ 1 qt./100 gal. + NIS @ 1 qt./100 gal.

HALEX GT @ 2.6 pt./A + ROUNDUP POWERMAX @ 32 oz./A +

6/12/2018 AMS @ 1 qt./100 gal. + NIS @ 1 qt./100 gal.

HAIL EVENT: June 6th - baseball sized hail with 3.19" of rainfall and 60 mph SPECIAL SEASONAL NOTES:

wind gusts resulting in significant crop injury, and loss of plant stand.

Weather, daytime temperatures and other factors affect data results, as in any year. The Irrigation Research Foundation strives to record and control these factors where possible. Not all of these factors are measurable or recognized.

For weather information please go to www.coagmet.com, monthly summaries, select the month, year and the Yuma station.		
VARIETIES	MOISTURE	BUSHELS PER ACRE
LG 53C50 STX	14.3	251.5
LG 54Co1 STX	14.5	254.4
LG 55C95 VT2 PRO + Capture @ 8.5 oz./A. APPLIED IN-FURROW	14.1	214.8
LG 5525 VT2 RIB + Capture @ 8.5 oz./A. APPLIED IN-FURROW	15.3	242.4
LG 58C77 VT2 PRO + Capture @ 8.5 oz./A. APPLIED IN-FURROW	15.3	234.6
LG 5565 STX RIB	16.5	233.9
LG 59C41 STX	16.6	254.5
LG 5548 STX RIB	16.6	219.6
LG 5590 VT2 RIB	16.9	241.5
LG 5606 STX RIB + Capture @ 8.5 oz./A. APPLIED IN-FURROW	17.7	252.8
LG 5618 STX RIB	18.7	231.4
LG 5624 STX RIB	16.7	225.5